

DS-PD1-PM-W

Wireless displacement detector



MAIN FEATURES

- Communication frequency: 433MHz, prevent from wireless data conflict
- Dual way communication, transmit distance around 500 meters (empty space)
- AES-128 encryption, safe and reliable
- CR2450 battery supply, around 1 year under normal condition

SPECIFICATIONS

Model	DS-PD1-PM-W
Emitting frequency	433MHz
Modulation	Frequency modulation
RF transmit distance	500m(empty space)
Tamper proof	Support
Working temperature	-10°C~55°C
Working humidity	10%~90%
Water proof	IP66
Dimension (mm)	60*31*10
Weight(g)	22

Model	DS-PD1-WL-W
Communication Frequency	433MHz
Modulation mode	Frequency
RF transmission distance	300m (open area)
Tamper Switch	YES
Detection method	Touch
Working Temperature	-10°C ~ +55°C
Working Humidity	≤95%RH
Dimensions (mm)	73 x 52 x 21
Weight (g)	64.5



CENTRAL SECURITY DISTRIBUTION

An Anixter Company

1300 319 499
csd.com.au

VIC: Mulgrave, Tullamarine NSW: Seven Hills, Waterloo ACT: Fyshwick QLD: Loganholme SA: Marleston WA: Balcatta