

English

1 APPEARANCE

- 1. Strobe Light 2. Buzzer 3. Cable Hole 4. Set Screw
- 5. Tamper Screw Hole 6. Tamper Button 7. Power Switch 8. Indicator

2 ENROLLMENT

3 INSTALLATION

- ★ Check signal strength.






User Manual

Scan the QR code for more information and operation help.

Specification

RF	Frequency	433 MHz
	Metod	Two-way communication
Indication	Distance	0.5 KM
	Indicator	Red/Green/Amber
Power	Strobe light	Red/Blue
	Power	Battery (default powersupply method)
	Consumption	Quiescent Current: 40 uA Max. 3 V/4 A (alerts in volume level 3)
	Low Battery Cut Off	2.45 V
	Voltage Range	Fully charged (new) to 2.45 V DC (battery)
Interface	Battery life span	3 CR123A, 3 years in work status (triggered every two weeks and alerting 90 s for each triggering)
	Power switch	Power switch
Buzzer	Tamper switch	Front and rear tamper-proof
	Decibel	90 to 110 db
General	Max. sound duration	15 min (900s)
	Operation Temperature	-10 °C to 40 °C (14°F to 104°F)
	Operation Humidity	10% to 90%
	Dimension (W x H x D)	88 x 88 x 32 mm (3.46" x 3.46" x 1.26")
	Weight	169.5 g
Installation	Wall mounting	

UD20459B-H



User Manual



English

The additional force shall be equal to three times the weight of the equipment but not less than 50N. The equipment and its associated mounting means shall remain secure during the installation. After the installation, the equipment, including any associated mounting plate, shall not be damaged. Install the device on the place with nonflammable surface, such as concrete wall.

Español

La fuerza adicional debe ser equivalente a tres veces el peso del equipo, pero no inferior a 50 N. El equipo y el soporte asociado deben permanecer seguros durante la instalación. Tras la instalación, no deberá dañarse el equipo ni las placas de montaje asociadas. Instale el dispositivo en una superficie no inflamable, por ejemplo, una pared de hormigón.

Português (Brasil)

A força adicional deve ser igual a três vezes o peso do equipamento, mas não inferior a 50 N. O equipamento e seus recursos de montagem associados devem permanecer seguros durante a instalação. Após a instalação, o equipamento, incluindo qualquer placa de montagem associada, não pode estar danificado. Instale o dispositivo notical com superfície não inflamável, como paredes de concreto.

Slovenščina

Dodatna sila morabil enaka trikratni teži opreme, vendar ne manjša od 50 N. Poskrbite, da med namestitvi ne poškodujete opreme in priloženih vgradnih pripomočkov. Po končan namestitvi ni pazite, da ne poškodujete opreme in morebitne vgradne plošče. Napravo namestite na mestu z neveljljivo površino, kot je betonska stena.

Srpski

Dodatna sila treba da bude jednaka trostrukoj težini opreme, ali ne manja od 50N. Oprema i odgovarajući pribor za postavljanje treba da budu pričvršćeni tokom postavljanja. Posle postavljanja, oprema i ploča za postavljanje koju ste koristili kontrolni ne smeju da budu oštećene. Uredaj instalirajte na mestu sa nezapaljivom površinom, kao što je betonski zid.

Türkçe

Ek karvet, ekipmanın ağırlığının üç katına eşit olmalı, ancak 50 N'den az olmamalıdır. Ekipman ve bağlı montaj araçları kurulum sırasında güvenli kalmalıdır. Kurulmadan sonra, ilgili montaj plakası da dahil, ekipman hasar görmemelidir. Çihazı, beton duvar gibi yanmaz yüzeye sahip bir yere monte edin.

ភាសាខ្មែរ

ចំនុចបន្ថែម ត្រូវស្មើនឹងបីដងនៃទម្ងន់របស់ឧបករណ៍ ប៉ុន្តែមិនតិចជាង 50N ទេ។ ឧបករណ៍ និងឧបករណ៍ភ្ជាប់មកជាមួយត្រូវរក្សាទុកស្ថេរ និងមិនត្រូវខូចខាត ក្នុងអំឡុងពេលដំឡើង។ បន្ទាប់ពីដំឡើងរួចរាល់ ឧបករណ៍ និងប្លាកភ្ជាប់មកជាមួយ មិនត្រូវខូចខាតឡើយ។ ត្រូវដំឡើងឧបករណ៍នៅលើផ្ទៃមិនឆេះ ដូចជាជញ្ជាំងបេតុង។

Hebrew

הקוח הנוסף חייב להיות שווה למשקל הציוד המותקן, אך לא פחות מ-50N. הציוד והציוד המותקן יחדיו יישארו בטוחים במהלך התהליך. לאחר ההתקנה, אין להזיק לציוד וללוח ההתקנה. יש להתקין את המכשיר על גבי משטח שאינו דליק, כגון קיר בטון.