



DS-PDC15-EG2-WB Wireless PIR Curtain Detector

DS-PDC15-EG2-WE is a two-way wireless detector featuring a solid curtain coverage up to 15m length by 3.6m height, it suitable for perimeter protection by setting up detection "curtain" walls or windows.




- Long range with narrow angle detection
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected
- Frequency hopping against jamming for reliable transmission





Lens Diagram



Specification

Detection Performance			
Detection Method	Passive Infrared		
Sensor Model	SFG321-711		
Detection Range	15m		
Detection Angle	6.3°		
Detection Zones	18		
Detectable Speed	0.3 to 2m/s		
Pet Immunity	None		
White Light Filter	6500lux		
Digital Temperature	Support		
Compensation	συμμοιτ		
Creep Zone Protection	Support		
Feature			
Digital Processing	Support		
Sealed Optics	Support		
Tamper Protection	Front,Rear		
Environment Temperature	Support		
Indicator	Support		
Signal Strength Indicator	Support		
Interface			
Power Switch	Power Up Enrolling		
LED Indicator	Blue(Alarm)		
Transmission			
Transmission Technology	Tri-X Wireless		
Transmission Method	Two-Way RF Wireless		
Transmission Frequency	433MHz		
Transmission Security	AES-128 Encryption		
Transmission Range(Free Space)	1.2Km		



Frequency Hopping	Support		
Enrolling Method	Power up,Remote ID,QR Code		
Electrical Characteristics			
Standard Battery Life	5 years in work status (being triggered 20 times per day)		
Power Supply	Battery Powered		
Battery Type	CR123A × 1		
Typical Voltage	3V		
General			
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)		
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)		
Operation Humidity	10% to 90%		
Dimension(WxHxD)	65.5mm × 103mm × 48.5mm		
Weight	128g		
Mounting Height	2.4 to 3.6m		
Mounting Method	Wall		
Application Scenario	Indoor		
Bracket	Optional Wall & Decessory		

Available Model

DS-PDC15-EG2-WB

Accessory

Optional

DS-PDB-IN-Wallbracket Internal ceiling mounted bracket	DS-PDP-IN-CR123A Indoor Detector Battery	DS-PDB-IN-Ceilingbracket Internal wall mounted bracket
	+ CR123A 3.0V -	





Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com

Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com

Hikvision UK & Ireland T+01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com

Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com

Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com