



DS-PDD12P-EG2-WB Wireless Dual-Tech Detector

DS-PDD12P-EG2-WB is a fully supervised two-way wireless detector featuring motion and microwave detection, tamper protection, low battery and supervision. It can operate for up to 5 years from two in-built batteies, and monitors the area within 12m radius, ingnores animals while recognizing human from the first step.

Key Features

- 3D optics including creep-zone protection, full coverage without dead angle
- 24G microwave to prevent wall penetration
- Digital temperature compensation
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected
- Frequency hopping against jamming for reliable transmission





Specification				
Detection Performance				
Detection Method	Passive Infrared, Microwave			
Sensor Model	SFG321-711			
Detection Range	12m			
Detection Angle	85.9°			
Detection Zones	52			
Detectable Speed	0.3 to 2m/s			
Sensitivity	Auto,High,Pet			
Pet Immunity	30Кg			
White Light Filter	6500lux			
Microwave Frequency	24GHz(24.15 ~ 24.25GHz)			
Digital Temperature Compensation	Support			
Creep Zone Protection	Support			
Feature				
Digital Processing	Support			
Sealed Optics	Support			
Tamper Protection	Front,Rear			
Environment Temperature	Support			
Indicator	заррон			
Signal Strength Indicator	Support			
Interface				
Power Switch	Power Up Enrolling			
LED Indicator	Green(PIR), Red(Microwave), Blue(Alarm)			
Transmission				
Transmission Technology	Tri-X Wireless			
Transmission Method	Two-Way RF Wireless			
Transmission Frequency	433MHz			
Transmission Security	AES-128 Encryption			
Transmission Range(Free Space)	1.2Km			
Frequency Hopping	Support			
Enrolling Method	Power up,Remote ID,QR Code			
Electrical Characteristics				
Standard Battery Life	5 years in work status (being triggered 20 times per day)			
Power Supply	Battery Powered			
Battery Type	CR123A × 2			
Typical Voltage	3V			
General				
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)			
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)			
Operation Humidity	10% to 90%			
Dimension(WxHxD)	65.5mm × 103mm × 48.5mm			



Weight	141g
Mounting Height	1.8 to 2.4m
Mounting Method	Wall
Application Scenario	Indoor
Bracket	Optional Wall & amp; Ceiling Accessory

• Available Model

DS-PDD12P-EG2-WB

• Accessory

• Optional

DS-PDB-IN-Ceilingbracket Internal wall mounted bracket	DS-PDP-IN-CR123A Indoor Detector Battery	DS-PDB-IN-Wallbracket Internal ceiling mounted bracket
	Literation Barriery Latero, + CR123A 3.0V - Bo Not Re-compet	





Distributed by

Γ

L



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T +1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com Hikvision BrazIl

T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T +601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hlkvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-(0)31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2020 | Data subject to change without notice |