



DS-PS1-E-WE Wireless External Sounder

The wireless external sounder, supporting 868 Mhz wireless communication, Tri-X wireless protocol, multiple enrollment methods, two-way wireless communication, multiple alarm sounds, and strobe light indication, is used for instant alarm alerting.

Key Features

- 868 MHz two-way wireless communication
- 3 years battery life span (triggered every two weeks and alerting 90 s for each triggering)
- AES-128 encryption
- Front and rear panel tamper-proof
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Buzzer Decibel: 110 dB
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission
- IP65 protective level

Available Model

• DS-PS1-E-WE





Frequency	868 MHz
Modulation	2GFSK
Method	Two-way communication
RF encryption	AES-128
RF distance	1.6 km (open area)
Power	Battery (default power supply method) or 12 VDC
Consumption	Static consumption: 30 to 40uA
Battery life span	4 CR123A, 3 years in work status
	(triggered every two weeks and
	alerting 90 s for each triggering)
Power switch	Supported
Tamper switch	Supported, Front and rear
	tamper-proof
Indicator	Indicator: Red/Green
	Strobe light: Red/Blue(white on the
	board)
Buzzer	Decibel: 110 dB
Operation temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation humidity	10% to 90% (no condensing)
Color	White
Material	PC+ABS
Dimension (W × H × D)	190× 200 × 47. 3mm .(7.48" ×7.87" ×
	1.86")
Weight	606.5 g (21.4 oz)
Protection level	IP65
Installation	Wall mounting
	Modulation Method RF encryption RF distance Power Consumption Battery life span Power switch Tamper switch Tamper switch Indicator Buzzer Operation temperature Operation temperature Operation humidity Color Material Dimension (W × H × D) Weight Protection level





Distributed by

Γ

L



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902

info.it@hikvision.com Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T+01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-(0)31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2019 | Data subject to change without notice |