

# DS-PK1-LRT-HWE/DS-PK1-LRT-HWB Wired keypad



The DS-PK1-LRT-HWE/DS-PK1-LRT-HWB wired keypad is an AX series keypad designed for AX hybrid pro control panel (DS-PHA48-EP, DS-PHA64-LP). The DS-PK1-LRT-HWE/DS-PK1-LRT-HWB supports built-in wireless transceiver and tag reader, which can work with keyfob and tag for arming/disarming.

- LCD screen display
- Supports one-touch arm (Arming without password)
- Supports fire/panic/medical alarm key
- Supports company name, phone number, time display
- Supports 2 on-board alarm inputs and 1 on-board alarm output
- Supports maximum 64 keyfobs





### Specification

Hardware features	DS-PK1-LRT-HWE	DS-PK1-LRT-HWB
Tag reader built in	1 built-in tag reader	
Serial port	1 TTL serial port	
Tamper-Proof	1 back-cover tamper-switch (Will be damaged when tamper triggered)	
Buzzer	1 on-board buzzer	
Function key	8 Function keys: Query, away arm, stay arm, disarm, alarm output, project, left, right	
RS-485	1 RS-485	
Alarm input	2 on-board alarm inputs	
Alarm output	1 on-board alarm output	
<b>Electrical characteristics</b>		
Power supply	DC 12 V	
Power consumption	Quiescent consumption: 0.984W @12 VDC	Quiescent consumption: 0.972W @12 VDC
	power supply with 82mA current	power supply with 81mA current
	Max consumption: 1.32W @12VDC power	Max consumption: 1.33W @12VDC power
	supply with 110mA current	supply with 111mA current
Wireless transmission		
RF frequency	868 MHz	433 MHz
Display		
Numeric key	0 to 9 , *, #	
Display screen	LCD screen	
Indicator	4 indicators and 1 backlight:	
	(1) Power: Green	
	(2) Faults: Fault-Orange / Alert-Flashing orange / Find me mode-flashing green	
	(3) Armed: Blue	
	(4) Alarm: Red	
	(5) Keypad button backlight: White	
General		
Dimension(W×H×D)	150 mm × 115 mm × 28 mm	
Color	White	
Operation temperature	- 10 °C to 55 °C (14 °F to 131 °F)	
Operation humidity	10% to 90%	
Device management		
Keyfob	64	

### Available Model

DS-PK1-LRT-HWE DS-PK1-LRT-HWB



Distributed by

## *HIKVISION*°

#### Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

**Hikvision Turkey** T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com **Hikvision Russia** T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com