



SPE-1630

16CH Video Encoder



Key Features

- Max. 5MP resolution
- Max. 12fps@5MP, 30fps@1080p
- H.265, H.264, MJPEG codec support
- Multiple streaming (up to 3 profiles per CH)
- 1 RJ-45 10/100/1000 Base-T

SPE-1630

16CH Video Encoder



Specifications

Video	
Input Channel	16CH BNC, 1.0Vp-p / 75Ω composite NTSC/PAL
Input Signal & Resolution	CVBS, AHD/CVI/TVI (1, 2, 4, 5MP) Auto Detection
Video Out	1 HDMI OUT (16 multi Image, 1920x1080)
Operational	
Motion Detection	Off / On
Privacy Masking	Off / On (4ea rectangular zones)
De-Interlacing	Support
Alarm I/O	16 Input/ 4 Output(1 NO/COM/NC, 3 NO/COM)
Alarm Trigger	Motion Detection, Alarm Input, Video Loss, Tampering, Network disconnect
Alarm Events	File Upload Via FTP, E-mail
Audio I/O	4 Line Input / 1 Line Output
OSD	Title, Date(Y/M/D), Time(H/M)
Remote Control Interface	1ea RS-485(Half Duplex)
RS-485 Protocol	SAMSUNG-T, PELCO-P/D
Coaxial Control	CVBS(Pelco-C) AHD, TVI, CVI
Network	
Ethernet	1 RJ-45 10/100/1000 Base-T
Video Compression Format	H.265, H.264 (MPEG-4 Part 10/AVC) : Main / Baseline / High, MJPEG
Resolution	2560x1920, 2560x1440, 1920x1080, 1280x720, 928x480(N), 928x240(N), 704x480(N), 704x240(N), 640x368, 352x240(N) 928x576(P), 928*288(P), 704x576(P), 704x288(P), 640x368, 352x288(P)
Max. Framerate	- Main Stream 5MP : 12fps/CH, 4MP : 15fps/CH(N), 12fps/CH(P) 1080p/720p/WD1/4CIF/CIF : 30fps/CH(N), 25fps/CH(P) - Sub Stream WD1/4CIF : 30fps/CH, 2CIF/CIF/QVGA/QCIF : 30fps/CH(N),25fps/CH(P), - MJPEG : 5fps @ 640x368,352x240, SD Camera : 5fps @ 480x240,352x240 ※ Enabling Time Display function in the OSD menu may cause up to 50 percent frame drop of the original setting.
Bitrate Control Method	H.265, H.264 : CBR or VBR
Streaming Capability	Multiple Streaming (Up to 3 Profiles per channel)
Audio Compression	G.711 u-law

Network

IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, ONVIF, Bonjour
Security	HTTPS (SSL) Login Authentication, Digest Login Authentication IP Address Filtering, User Access Log, 802.1X Authentication (EAP-TLS, EAP-LEAP)
Streaming Method	Unicast / Multicast
Max. User Access	rtp/rtsp max. 48 users(4 Users/CH) at Unicast Mode , http max.32 users
Webpage Language	English, French, German, Spanish, Italian, Russian, Turkish, Polish, Dutch, Swedish, Portuguese, Czech, Chinese, Japanese, Korean, Hungarian, Greek
Web Viewer	Supported OS: Windows 10 or later,Windows 7,8,10,Mac OS X 10.13 or later, Non-plugin WebViewer Supported Browser: Google Chrome 80 or later,MS Edge 83 or later,Mozilla Firefox 72 or later,Apple Safari 11.0.1 or later
Application Programming Interface	ONVIF profile S, SUNAPI (HTTP API)
Compatible Software & Recorder	SmartViewer, SSM, NVR(Hanwha Techwin, P/X/Q/L series)

Environmental

Operating Temperature / Humidity	-10°C ~ +50°C / 20% ~ 80% RH (-10°C ~ +40°C when installed in RACK)
----------------------------------	---

Electrical

Input Voltage / Current	DC12V/5A
Power Consumption	MAX : 20.0W (12V, 1.67A)

Mechanical

Color/Metal	Black / Metal
Dimension(WxHxD)	370.0 × 44.0 x 320.0(include Connector 330.9)mm
Weight	2.32kg(5.115lb)

SPE-1630

16CH Video Encoder



CAD

Unit: mm [inch]

